

SurfaPaint™ ThermoDry Interior

High-quality, thermal protective, water-based paint for interior walls & ceilings

Product Description

SurfaPaint™ ThermoDry Interior is a high-quality acrylic water paint with heat protective properties, ideal for indoor use enhanced with SurfaPaint™ ThermoDry technology. Its composition prevents heat transfer due to low thermal conductivity of the material, resulting in significant energy savings during winter and summer. SurfaPaint™ ThermoDry Interior is followed by excellent coverage and washability, strong adhesion, elasticity, antifungal action and water repellent. It is an ideal solution to prevent the growth of mold, as it prevents the formation of thermal bridges and minimizes the condensation of moisture on cold surfaces of the walls.

Recommended Use

It is ideal for houses, areas vulnerable to water vapor condensation and mold growth (sloping surfaces, bathrooms, kitchens, etc.) but also for public buildings, hospitals, offices, etc. Suitable for any type of new or old surface such as concrete, plaster, plasterboard and wood.

Key Benefits

- ☆ Heat protection and energy savings, contributes to the energy upgrade of the building
- ☆ Formation of thermal bridges is prevented
- ☆ Excellent coverage, strong adhesion and elasticity
- ☆ Long-life without repainting
- ☆ Water-based paint with low odor, VOC and environmentally friendly
- ☆ Easy-to-apply with wonderful matte finish
- ☆ Enhanced protection against microorganisms and fungi
- ☆ High permeability

Approved by the organization European Cool Roofs Council (ECRC)

Product ID: FA00000005

ECRC EUROPEAN COOLROOFS COUNCIL		Rated Product ID Number FA00000005	
RATED PRODUCT	Initial	Aged	
Solar Reflectance	0.85	-	
Infrared Emittance	0.89	-	
Solar Reflectance Index	107	-	
Climate type	Date of measurement	Manufacturers name	
-	11/12/2015	NanoPhos SA	

European Cool Roofs Council Ratings are determined for a fixed set of conditions which may not be appropriate for determining differing seasonal performance. The actual effect of color reflectance and thermal emittance on building performance may vary with differing conditions. The manufacturer of this product stipulates that these ratings were determined in accordance with the applicable European Cool Roofs Council procedures.



NanoPhos S.A.

PO Box 519, Sci. & Tech. Park of Lavrio, 1st Km. Lavrio - Athens Ave., 19500 Lavrio, Greece
T. (+30) 22920 69312 | F. (+30) 22920 69303 | E. info@nanophos.com | W. www.NanoPhos.com

SurfaPaint™ ThermoDry Interior

High-quality, thermal protective, water-based paint for interior walls & ceilings

Technical Specifications

Type	▶	Water-based, 100% acrylic
Color	▶	white – available for tinting in P & D bases for light shades
Density	▶	1.05±0.05 kg/L
pH	▶	9.0 ± 0.5
VOC (Volatile Organic Compounds)	▶	10 g/L ¹
Dilution	▶	Up to 10% with water
Viscosity	▶	110±10 KU
Solid content (% v/v)	▶	50±5%
Touch-dry time	▶	30min @20°C
Drying time	▶	1h @20°C
Min. Recoat Interval	▶	4-6h @20°C
Reflectance (ASTM G 173)	▶	TSR: 90.5% (280-2200nm) NIR: 94.19% (700nm-2200nm) VIS: 94.04% (380-780nm)
Thermal conductivity (EN ISO 12667:2004)	▶	0.096 W/(mK)
IR Emittance Factor (ASTM E408-71)	▶	ε= 0.91
Washability (ISO 11998:2006)	▶	Κλάση II

¹ EU limit value (Directive 2004/42 / EC) of the product ready for use (Category A / c "For external walls of mineral substrate", Type Y): 40 g / L (2010). The maximum VOC content of this product is 10 g/L.

(*) Dry to recoat time is prolonged under low temperature and high humidity

Surface Preparation

All surfaces must be clean, dry and free of dust, oils, grease and loose residue. New cement substrates and new masonry should have matured for more than 3-4 weeks before applying the primer. For best results use the NanoPhos Primer SurfaMix™ P.

Application Instructions

Shake well before use. No dilution is required to cover capillary cracks up to 0.5 mm. For cracks larger than 1mm, cover the gap with a suitable putty. If dilution is required, add up to 10% water by volume. The application temperature should be between 8 - 35°C. Apply 2-3 coats using a good quality brush, roller or spray with a nozzle diameter of 1.4 mm or more. Do not add more than recommended. Make sure the corners and edges are adequately covered. After use, clean the tools with water immediately.

Spreading Rate

10-12 m²/L, depending on the absorbance of surface application.

NanoPhos S.A.

PO Box 519, Sci. & Tech. Park of Lavrio, 1st Km. Lavrio - Athens Ave., 19500 Lavrio, Greece
T. (+30) 22920 69312 | F. (+30) 22920 69303 | E. info@nanophos.com | W. www.NanoPhos.com

SurfaPaint™ ThermoDry Interior

High-quality, thermal protective, water-based paint for interior walls & ceilings

Storage

Storage in the original closed package, in a well-ventilated area, at a temperature of 5oC to 35oC, away from sunlight and frost. Inclement storage conditions may affect product quality.

Health & Safety

Read the label of the product before use. Safety Data Sheet is available through NanoPhos' website www.NanoPhos.com or upon request by contacting NanoPhos through email: info@NanoPhos.com or by telephone: (+30) 2292069312.

Available Packaging

- 3L Plastic Container
- 10L Plastic Container

Available in bases for tinting

Base P

- 2.91L Plastic Container
- 9.70L Plastic Container

Base D

- 2.85L Plastic Container
- 9.50L Plastic Container

Disclaimer: The Technical Data Sheet recommendations for the use of NanoPhos' products are based on our scientific knowledge, laboratory studies and long-term experience. The information provided must be considered indicative and subject to constant review based on specific conditions and each practical application. The suitability of the product should be examined in each case for specific use and the end user bears full & exclusive responsibility for any side effects that may arise from the incorrect use of the product. The present edition of this technical datasheet automatically cancels any previous one concerning the same product. For more information please contact NanoPhos: info@NanoPhos.com

SurfaPaint™ logo is a registered trademark of NanoPhos SA

NanoPhos S.A.

PO Box 519, Sci. & Tech. Park of Lavrio,1st Km. Lavrio - Athens Ave., 19500 Lavrio, Greece
T. (+30) 22920 69312 | F. (+30) 22920 69303 | E. info@nanophos.com | W. www.NanoPhos.com