

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: NanoPhos\_07022023-001  
Product name: SurfaDur P Pool, Part A  
UFI: 5RSV-C03W-900Y-6X13

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: not available

#### 1.3. Details of the supplier of the safety data sheet

Name: NANOPHOS S.A.  
Full address: Technological & Cultural Park  
District and Country: 19 500 Lavrio (Greece)  
Greece  
Tel. +30 22920 69312  
Fax +30 22920 69303

e-mail address of the competent person

responsible for the Safety Data Sheet: iarabatz@NanoPhos.com  
Supplier: Ioannis Arabatzis

#### 1.4. Emergency telephone number

For urgent inquiries refer to: +30 22920 69312

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

|  |      |  |
|--|------|--|
| Skin sensitization, category 1                                     | H317 | May cause an allergic skin reaction.               |
| Hazardous to the aquatic environment, chronic toxicity, category 3 | H412 | Harmful to aquatic life with long lasting effects. |

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

## SurfaDur P Pool, Part A



Signal words: Warning

Hazard statements:

**H317** May cause an allergic skin reaction.  
**H412** Harmful to aquatic life with long lasting effects.

Precautionary statements:

**P280** Wear protective gloves.  
**P321** Specific treatment (see . . . on this label).  
**P272** Contaminated work clothing should not be allowed out of the workplace.  
**P501** Dispose of contents or container according to local/national/international regulations  
**P102** Keep out of reach of children.  
**P101** If medical advice is needed, have product container or label at hand.  
**P261** Avoid breathing fume, mist or spray.  
**P333+P313** If skin irritation or rash occurs: Get medical advice / attention.  
**P362+P364** Take off contaminated clothing and wash it before reuse.  
**P273** Avoid release to the environment.

**Contains:** Aspartic Acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester  
 Aspartic Acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester  
 Aspartic Ester  
 4-morpholinecarbaldehyde  
 Fumaric acid diethyl ester

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition : 80,00  
 Limit value: 500,00

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration greater than 0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

| Identification   | x = Conc. % | Classification (EC) 1272/2008 (CLP)       |
|--|-------------|---|
| Aspartic Acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester<br>INDEX 607-350-00-9 | 10 < x < 25 | Skin Sens. 1 H317, Aquatic Chronic 3 H412 |

SurfaDur P Pool, Part A

EC 412-060-9

CAS 136210-32-7

**Aspartic Ester**

INDEX 10 < x < 25

EC -

CAS 152637-10-0

**Aspartic Acid, N,N'-(methylenedi-4,1-cyclohexanediy)bis-, 1,1',4,4'-tetraethyl ester**

INDEX 607-521-00-8 5 < x < 10

EC 429-270-1

CAS 136210-30-5

**Fumaric acid diethyl ester**

INDEX - 0 < x < 1

EC 210-819-7

CAS 623-91-6

**4-morpholinecarbaldehyde**

INDEX - 0 < x < 1

EC 224-518-3

CAS 4394-85-8

Skin Sens. 1B H317, Aquatic Chronic 3 H412

Skin Sens. 1 H317, Aquatic Chronic 3 H412

Acute Tox. 4 H302, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317  
LD50 Oral: 1367 mg/kg

Skin Sens. 1B H317

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures**

**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures**

**5.1. Extinguishing media**

**SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection**

**8.1. Control parameters**

**Aspartic Acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester**

Predicted no-effect concentration - PNEC

|  |          |       |
|--|----------|-------|
| Normal value in fresh water                  | 0,00013  | mg/l  |
| Normal value in marine water                 | 0,000013 | mg/l  |
| Normal value for fresh water sediment        | 0,21     | mg/kg |
| Normal value for marine water sediment       | 0,02     | mg/kg |
| Normal value of STP microorganisms           | 31,1     | mg/l  |
| Normal value for the terrestrial compartment | 0,1      | mg/kg |

**Health - Derived no-effect level - DNEL / DMEL**

| Route of exposure | Effects on consumers |                |               | Effects on workers |             |                |               |                  |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
|                   | Acute local          | Acute systemic | Chronic local | Chronic systemic   | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral              |                      | 4,2 mg/kg bw/d |               | 4,2 mg/kg bw/d     |             |                |               |                  |
| Inhalation        | NPI                  | 14,5 mg/m3     | NPI           | 14,5 mg/m3         | NPI         | 672 mg/m3      | NPI           | 84 mg/m3         |
| Skin              | MED                  | 4,2 mg/kg bw/d | MED           | 4,2 mg/kg bw/d     | MED         | NPI            | MED           | 11,9 mg/kg bw/d  |

**Aspartic Acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester**

Predicted no-effect concentration - PNEC

|  |          |       |
|--|----------|-------|
| Normal value in fresh water                  | 0,00013  | mg/l  |
| Normal value in marine water                 | 0,000013 | mg/l  |
| Normal value for fresh water sediment        | 0,21     | mg/kg |
| Normal value for marine water sediment       | 0,02     | mg/kg |
| Normal value of STP microorganisms           | 31,1     | mg/l  |
| Normal value for the terrestrial compartment | 0,1      | mg/kg |
| Normal value for the atmosphere              | NPI      |       |

**Health - Derived no-effect level - DNEL / DMEL**

| Route of exposure | Effects on consumers |                |               | Effects on workers |             |                |               |                  |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
|                   | Acute local          | Acute systemic | Chronic local | Chronic systemic   | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral              |                      | 1,4 mg/kg bw/d |               | 1,4 mg/kg bw/d     |             |                |               |                  |
| Inhalation        | NPI                  | 4,8 mg/m3      | NPI           | 4,8 mg/m3          | NPI         | 112 mg/m3      | NPI           | 28 mg/m3         |
| Skin              |                      | 1,4 mg/kg bw/d |               | 1,4 mg/kg bw/d     |             | NPI            |               | 4 mg/kg bw/d     |

**4-morpholinecarbaldehyde**

Predicted no-effect concentration - PNEC

|  |        |       |
|--|--------|-------|
| Normal value in fresh water                  | 0,5    | mg/l  |
| Normal value in marine water                 | 0,05   | mg/l  |
| Normal value for fresh water sediment        | 1,85   | mg/kg |
| Normal value for marine water sediment       | 0,0764 | mg/kg |
| Normal value for water, intermittent release | 5      | mg/l  |
| Normal value of STP microorganisms           | 2000   | mg/l  |

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

**SECTION 9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

| Properties                     | Value                         | Information |
|--------------------------------|-------------------------------|-------------|
| Appearance                     | liquid                        |             |
| Colour                         | Blue/ Light Blue/ Grey/ White |             |
| Odour                          | Sand/ White                   |             |
| Melting point / freezing point | not available                 |             |
| Initial boiling point          | not available                 |             |
| Flammability                   | not available                 |             |
| Lower explosive limit          | not available                 |             |
| Upper explosive limit          | not available                 |             |
| Flash point                    | > 60 °C                       |             |

|  |                |
|--|----------------|
| Auto-ignition temperature              | not available  |
| Decomposition temperature              | not available  |
| pH                                     | not applicable |
| Kinematic viscosity                    | not available  |
| Solubility                             | not available  |
| Partition coefficient: n-octanol/water | not available  |
| Vapour pressure                        | not available  |
| Density and/or relative density        | not available  |
| Relative vapour density                | not available  |
| Particle characteristics               | not applicable |

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

Information not available

### 9.2.2. Other safety characteristics

Information not available  
VOC (Directive 2010/75/EU)

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials

Information not available

### 10.6. Hazardous decomposition products

Information not available

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

#### Information on likely routes of exposure

Information not available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

#### Interactive effects

Information not available

#### ACUTE TOXICITY

|                                  |   |
|----------------------------------|---|
| ATE (Inhalation) of the mixture: | Not classified (no significant component) |
| ATE (Oral) of the mixture:       | Not classified (no significant component) |
| ATE (Dermal) of the mixture:     | Not classified (no significant component) |

Aspartic Acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester

|                |              |
|----------------|--------------|
| LD50 (Dermal): | > 2000 mg/kg |
| LD50 (Oral):   | > 2000 mg/kg |

Aspartic Ester

|                |                  |
|----------------|------------------|
| LD50 (Dermal): | > 2000 mg/kg Rat |
| LD50 (Oral):   | > 2000 mg/kg Rat |

Aspartic Acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester



**SurfaDur P Pool, Part A**

LD50 (Dermal): > 2000 mg/kg Rat  
LD50 (Oral): > 2000 mg/kg Rat

Fumaric acid diethyl ester

LD50 (Oral): 1367 mg/kg

4-morpholinecarbaldehyde

LD50 (Dermal): > 18400 mg/kg Rabbit  
LD50 (Oral): > 7360 mg/kg Rat

**SKIN CORROSION / IRRITATION**

Does not meet the classification criteria for this hazard class

**SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

**RESPIRATORY OR SKIN SENSITISATION**

Sensitising for the skin

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

#### 12.1. Toxicity

Aspartic Acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester

LC50 - for Fish 66 mg/l/96h

EC50 - for Crustacea

> 88,6 mg/l/48h

Aspartic Acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester

LC50 - for Fish

66 mg/l/96h Danio rerio

EC50 - for Crustacea

88,6 mg/l/48h Daphnia magna

Aspartic Ester

LC50 - for Fish

66 mg/l/96h Danio rerio

EC50 - for Crustacea

> 100 Daphnia magna

4-morpholinecarbaldehyde

LC50 - for Fish

> 500 mg/l/96h Leuciscus idus (Golden orfe)

EC50 - for Crustacea

> 500 mg/l/48h Daphnia magna (Water flea)

EC50 - for Algae / Aquatic Plants

23880 mg/l/72h Scenedesmus subspicatus

EC10 for Algae / Aquatic Plants

17040 mg/l/72h Scenedesmus subspicatus

#### 12.2. Persistence and degradability

Aspartic Ester

NOT rapidly degradable

4-morpholinecarbaldehyde

Rapidly degradable

### 12.3. Bioaccumulative potential

Information not available

### 12.4. Mobility in soil

Information not available

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

### 12.7. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

### 14.1. UN number or ID number

not applicable

### 14.2. UN proper shipping name

not applicable

**14.3. Transport hazard class(es)**

not applicable

**14.4. Packing group**

not applicable

**14.5. Environmental hazards**

not applicable

**14.6. Special precautions for user**

not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

|                          |  |
|--------------------------|--|
| <b>Acute Tox. 4</b>      | Acute toxicity, category 4   |
| <b>Skin Irrit. 2</b>     | Skin irritation, category 2  |
| <b>STOT SE 3</b>         | Specific target organ toxicity - single exposure, category 3       |
| <b>Skin Sens. 1</b>      | Skin sensitization, category 1                                     |
| <b>Skin Sens. 1B</b>     | Skin sensitization, category 1B                                    |
| <b>Aquatic Chronic 3</b> | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| <b>H302</b>              | Harmful if swallowed.  |
| <b>H315</b>              | Causes skin irritation.  |
| <b>H335</b>              | May cause respiratory irritation.                                  |
| <b>H317</b>              | May cause an allergic skin reaction.                               |
| <b>H412</b>              | Harmful to aquatic life with long lasting effects.                 |

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
  22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: NanoPhos\_22032023-001  
 Product name: SurfaDur P Pool, Part B  
 UFI: 8WSV-C0GP-W00Y-HM67

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: not available

#### 1.3. Details of the supplier of the safety data sheet

Name: NANOPHOS S.A.  
 Full address: Technological & Cultural Park  
 District and Country: 19 500 Lavrio (Greece)  
 Greece

Tel. +30 22920 69312

Fax +30 22920 69303

e-mail address of the competent person

responsible for the Safety Data Sheet: iarabatz@NanoPhos.com  
 Supplier: Ioannis Arabatzis

#### 1.4. Emergency telephone number

For urgent inquiries refer to: +30 22920 69312

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

|  |      |  |
|--|------|--|
| Flammable liquid, category 3                                       | H226 | Flammable liquid and vapour.                     |
| Acute toxicity, category 4   | H332 | Harmful if inhaled.                              |
| Specific target organ toxicity - single exposure, category 3       | H335 | May cause respiratory irritation.                |
| Skin sensitization, category 1                                     | H317 | May cause an allergic skin reaction.             |
| Hazardous to the aquatic environment, chronic toxicity, category 2 | H411 | Toxic to aquatic life with long lasting effects. |

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



SurfaDur P Pool, Part B

Hazard pictograms:



Signal words: Warning

Hazard statements:

**H226** Flammable liquid and vapour.  
**H332** Harmful if inhaled.  
**H335** May cause respiratory irritation.  
**H317** May cause an allergic skin reaction.  
**H411** Toxic to aquatic life with long lasting effects.  
**EUH066** Repeated exposure may cause skin dryness or cracking.  
**EUH204** Contains isocyanates. May produce an allergic reaction.

Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P370+P378** In case of fire: use dry powder or Carbon Dioxide (CO<sub>2</sub>) fire extinguisher to extinguish.  
**P273** Avoid release to the environment.  
**P391** Collect spillage.  
**P321** Specific treatment (see . . . on this label).  
**P242** Use non-sparking tools.  
**P403+P235** Store in a well-ventilated place. Keep cool.  
**P303+P361+P353** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
**P304+P340** IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
**P240** Ground and bond container and receiving equipment.  
**P243** Take action to prevent static discharges.  
**P241** Use explosion-proof [electrical / ventilating / lighting / . . . ] equipment.  
**P272** Contaminated work clothing should not be allowed out of the workplace.  
**P501** Dispose of contents or container according to local/national/international regulations  
**P103** Read label before use.  
**P102** Keep out of reach of children.  
**P101** If medical advice is needed, have product container or label at hand.  
**P261** Avoid breathing fume, mist or spray.  
**P312** Call a POISON CENTRE or a doctor if you feel unwell.  
**P403+P233** Store in a well-ventilated place. Keep container tightly closed.  
**P362+P364** Take off contaminated clothing and wash it before reuse.  
**P271** Use only outdoors or in a well-ventilated area.  
**P405** Store locked up.

**Contains:** hexamethylene-1,6-diisocyanate homopolymer  
 Aliphatic Polyisocyanate 1  
 Aliphatic Polyisocyanate 2  
 XYLENE, mixed isomers

As from 24 August 2023 adequate training is required before industrial or professional use.

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition : 80,00  
 Limit value: 500,00

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration greater than 0.1%.

**SECTION 3. Composition/information on ingredients**

**3.2. Mixtures**

Contains:

| Identification                                    | x = Conc. % | Classification (EC) 1272/2008 (CLP)  |
|---|-------------|--|
| <b>hexamethylene-1,6-diisocyanate homopolymer</b> |             |  |
| INDEX -   | 50 < x < 70 | Acute Tox. 4 H332, STOT SE 3 H335, Skin Sens. 1 H317   |
| EC 500-060-2                                      |             | STA Inhalation mists/powders: 1,5 mg/l   |
| CAS 28182-81-2                                    |             |  |
| <b>Aliphatic Polyisocyanate 1</b>                 |             |  |
| INDEX -   | 10 < x < 20 | Acute Tox. 4 H332, STOT SE 3 H335, Skin Sens. 1B H317, Aquatic Chronic 2 H411  |
| EC 642-404-5                                      |             | STA Inhalation mists/powders: 1,5 mg/l   |
| CAS 164250-92-4                                   |             |  |
| <b>N-BUTYL ACETATE</b>                            |             |  |
| INDEX 607-025-00-1                                | 10 < x < 20 | Flam. Liq. 3 H226, STOT SE 3 H336, EUH066  |
| EC 204-658-1                                      |             |  |
| CAS 123-86-4                                      |             |  |
| <b>Aliphatic Polyisocyanate 2</b>                 |             |  |
| INDEX   | 5 < x < 10  | Acute Tox. 4 H332, STOT SE 3 H335, Skin Sens. 1B H317, Aquatic Chronic 2 H411  |
| EC -  |             | STA Inhalation mists/powders: 1,5 mg/l   |
| CAS 29891-05-2                                    |             |  |
| <b>XYLENE, mixed isomers</b>                      |             |  |
| INDEX 601-022-00-9                                | 0 < x < 5   | Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C |
| EC 215-535-7                                      |             | STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l  |
| CAS 1330-20-7                                     |             |  |
| <b>Aliphatic Polyisocyanate 3</b>                 |             |  |
| INDEX   | 0 < x < 1   | Acute Tox. 4 H332, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Chronic 2 H411   |
| EC -  |             | STA Inhalation mists/powders: 1,5 mg/l   |
| CAS 1809331-98-3                                  |             |  |
| <b>hexamethylene-di-isocyanate</b>                |             |  |
| INDEX 615-011-00-1                                | 0 < x < 0,5 | Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317   |
| EC -  |             | Skin Sens. 1 H317:   |
|   |             | 0,5%, Resp. Sens. 1 H334:  |
|   |             | 0,5%   |
| CAS 822-06-0                                      |             | LD50 Oral: 738 mg/kg, STA Inhalation vapours: 11 mg/l  |
| REACH Reg. 01-2119457571-37-                      |             |  |

0000, 01-2119457571-37-0005, 01-2119457571-37-0006

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

## SurfaDur P Pool, Part B

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

|     |                |   |
|-----|----------------|---|
| FRA | France         | Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS  |
| GRC | Ελλάδα         | Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία``» |
| ROU | România        | Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006   |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020)   |
| EU  | OEL EU         | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.  |
|     | TLV-ACGIH      | ACGIH 2022  |

SurfaDur P Pool, Part B

**hexamethylene-1,6-diisocyanate homopolymer**

Predicted no-effect concentration - PNEC

|  |        |       |
|--|--------|-------|
| Normal value in fresh water            | 0,127  | mg/l  |
| Normal value in marine water           | 0,0127 | mg/l  |
| Normal value for fresh water sediment  | 266701 | mg/kg |
| Normal value for marine water sediment | 26670  | mg/kg |
| Normal value of STP microorganisms     | 88     | mg/l  |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers |                |               |                  | Effects on workers |                |               |                  |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------|
|                   | Acute local          | Acute systemic | Chronic local | Chronic systemic | Acute local        | Acute systemic | Chronic local | Chronic systemic |
| Inhalation        |                      |                |               |                  | 1 mg/m3            | NPI            | 0,5 mg/m3     | NPI              |
| Skin              |                      |                |               |                  |                    | NPI            |               | NPI              |

**N-BUTYL ACETATE**

Threshold Limit Value

| Type      | Country | TWA/8h |     | STEL/15min |     | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
|           |         | mg/m3  | ppm | mg/m3      | ppm |                        |
| VLEP      | FRA     | 710    | 150 | 940        | 200 |                        |
| TLV       | GRC     | 710    | 150 | 950        | 200 |                        |
| TLV       | ROU     | 241    | 50  | 723        | 150 |                        |
| WEL       | GBR     | 724    | 150 | 966        | 200 |                        |
| OEL       | EU      | 241    | 50  | 723        | 150 |                        |
| TLV-ACGIH |         |        | 50  |            | 150 |                        |

Predicted no-effect concentration - PNEC

|  |        |       |
|--|--------|-------|
| Normal value in fresh water                  | 0,18   | mg/l  |
| Normal value in marine water                 | 0,018  | mg/l  |
| Normal value for marine water sediment       | 0,0981 | mg/kg |
| Normal value for water, intermittent release | 0,981  | mg/l  |
| Normal value of STP microorganisms           | 35,6   | mg/l  |
| Normal value for the terrestrial compartment | 0,0903 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers |                |               |                  | Effects on workers |                |               |                  |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------|
|                   | Acute local          | Acute systemic | Chronic local | Chronic systemic | Acute local        | Acute systemic | Chronic local | Chronic systemic |
| Oral              |                      |                |               | 3.4 mg/kg bw/d   |                    |                |               |                  |
| Inhalation        | 859.7 mg/m3          | 859.7 mg/m3    | 102.34 mg/m3  | 102.34 mg/m3     | 960 mg/m3          | 960 mg/m3      | 480 mg/m3     | 480 mg/m3        |
| Skin              |                      |                |               | 3.4 mg/kg bw/d   |                    |                |               | 7 mg/kg bw/d     |

**XYLENE, mixed isomers**

Threshold Limit Value

| Type | Country | TWA/8h |     | STEL/15min |     | Remarks / Observations |
|------|---------|--------|-----|------------|-----|------------------------|
|      |         | mg/m3  | ppm | mg/m3      | ppm |                        |
| VLEP | FRA     | 221    | 50  | 442        | 100 | SKIN                   |
| TLV  | GRC     | 435    | 100 | 650        | 150 |                        |

|           |     |     |     |     |     |      |
|-----------|-----|-----|-----|-----|-----|------|
| TLV       | ROU | 221 | 50  | 442 | 100 | SKIN |
| WEL       | GBR | 220 | 50  | 441 | 100 | SKIN |
| OEL       | EU  | 221 | 50  | 442 | 100 | SKIN |
| TLV-ACGIH |     | 434 | 100 | 651 | 150 |      |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

**SECTION 9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

| Properties                             | Value          | Information |
|--|----------------|-------------|
| Appearance                             | liquid         |             |
| Colour                                 | transparent    |             |
| Odour                                  | not available  |             |
| Melting point / freezing point         | not available  |             |
| Initial boiling point                  | not available  |             |
| Flammability                           | not available  |             |
| Lower explosive limit                  | not available  |             |
| Upper explosive limit                  | not available  |             |
| Flash point                            | 23 < T< 60 °C  |             |
| Auto-ignition temperature              | not available  |             |
| Decomposition temperature              | not available  |             |
| pH                                     | not available  |             |
| Kinematic viscosity                    | not available  |             |
| Solubility                             | not available  |             |
| Partition coefficient: n-octanol/water | not available  |             |
| Vapour pressure                        | not available  |             |
| Density and/or relative density        | not available  |             |
| Relative vapour density                | not available  |             |
| Particle characteristics               | not applicable |             |

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

Information not available

### 9.2.2. Other safety characteristics

Information not available

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### N-BUTYL ACETATE

Decomposes on contact with: water.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

#### XYLENE, mixed isomers

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

#### N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

#### 10.5. Incompatible materials

#### N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

N-BUTYL ACETATE



SurfaDur P Pool, Part B

WORKERS: inhalation; contact with the skin.

XYLENE, mixed isomers

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

XYLENE, mixed isomers

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

XYLENE, mixed isomers

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

|  |   |
|--|---|
| ATE (Inhalation - mists / powders) of the mixture: | 1,50 mg/l                                 |
| ATE (Inhalation - vapours) of the mixture:         | Acute Tox. 4                              |
| ATE (Inhalation - gas) of the mixture:             | Acute Tox. 4                              |
| ATE (Oral) of the mixture:                         | Not classified (no significant component) |
| ATE (Dermal) of the mixture:                       | >2000 mg/kg                               |

hexamethylene-1,6-diisocyanate homopolymer

|                                  |   |
|----------------------------------|---|
| LD50 (Dermal):                   | > 2000 mg/kg Rabbit   |
| LD50 (Oral):                     | > 5000 mg/kg rat  |
| LC50 (Inhalation mists/powders): | 0,554 mg/l/4h Rat, male/female  |
| STA (Inhalation mists/powders):  | 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP<br>(figure used for calculation of the acute toxicity estimate of the mixture) |

Aliphatic Polyisocyanate 1

## SurfaDur P Pool, Part B

LD50 (Dermal): > 2000 mg/kg Rat  
LD50 (Oral): > 5000 mg/kg Rat  
LC50 (Inhalation mists/powders): 0,351 mg/l/4h Rat, male  
STA (Inhalation mists/powders): 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

## N-BUTYL ACETATE

LD50 (Dermal): > 5000 mg/kg Rabbit  
LD50 (Oral): > 6400 mg/kg Rat  
LC50 (Inhalation vapours): 21,1 mg/l/4h Rat

## Aliphatic Polyisocyanate 2

LD50 (Dermal): > 2000 mg/kg Rat  
LD50 (Oral): > 5000 mg/kg Rat  
LC50 (Inhalation mists/powders): 0,351 mg/l/4h Rat, male  
STA (Inhalation mists/powders): 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

## XYLENE, mixed isomers

LD50 (Dermal): 4350 mg/kg Rabbit  
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)  
LD50 (Oral): 3523 mg/kg Rat  
LC50 (Inhalation vapours): 26 mg/l/4h Rat  
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

## Aliphatic Polyisocyanate 3

LD50 (Dermal): > 2000 mg/kg Rat  
LD50 (Oral): > 2000 mg/kg Rat  
LC50 (Inhalation mists/powders): 0,351 mg/l/4h Rat, male

## hexamethylene-di-isocyanate

LD50 (Dermal): > 7000 mg/kg Rabbit  
LD50 (Oral): 738 mg/kg Rat  
LC50 (Inhalation vapours): 0,124 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

XYLENE, mixed isomers

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

### 12.1. Toxicity

hexamethylene-1,6-diisocyanate

homopolymer

LC50 - for Fish

> 100 mg/l/96h Danio rerio (zebra fish)

EC50 - for Crustacea

> 100 mg/l/48h Daphnia magna (water flea)

EC50 - for Algae / Aquatic Plants

> 50 mg/l/72h Scenedesmus Subspicatus

hexamethylene-di-isocyanate

LC50 - for Fish

26,1 mg/l/96h static (Brachydanio rerio)

Aliphatic Polyisocyanate 1

LC50 - for Fish

89 mg/l/96h Species: Danio rerio (zebra flish)

EC50 - for Crustacea

> 100 mg/l/48h Species: Daphnia Magna (Water flea)

Aliphatic Polyisocyanate 2

LC50 - for Fish

8,9 mg/l/96h Danio rerio (zebra fish)

EC50 - for Crustacea

> 100 mg/l/48h Daphnia Magna (Water flea)

Aliphatic Polyisocyanate 3

LC50 - for Fish

8,9 mg/l/96h Danio rerio (zebra fish)

EC50 - for Crustacea

> 100 mg/l/48h Daphnia magna (Water flea)

### 12.2. Persistence and degradability

XYLENE, mixed isomers

Solubility in water

100 - 1000 mg/l

Rapidly degradable

N-BUTYL ACETATE

Solubility in water

1000 - 10000 mg/l

hexamethylene-1,6-diisocyanate

homopolymer

NOT rapidly degradable

Aliphatic Polyisocyanate 2

NOT rapidly degradable

Aliphatic Polyisocyanate 3

NOT rapidly degradable

### 12.3. Bioaccumulative potential

XYLENE, mixed isomers

Partition coefficient: n-octanol/water

3,12

BCF

25,9

N-BUTYL ACETATE

|  |      |
|--|------|
| Partition coefficient: n-octanol/water | 2,3  |
| BCF                                    | 15,3 |

**12.4. Mobility in soil**

XYLENE, mixed isomers

|                                   |      |
|-----------------------------------|------|
| Partition coefficient: soil/water | 2,73 |
|-----------------------------------|------|

N-BUTYL ACETATE

|                                   |     |
|-----------------------------------|-----|
| Partition coefficient: soil/water | < 3 |
|-----------------------------------|-----|

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations**

**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information**

**14.1. UN number or ID number**

|                        |      |
|------------------------|------|
| ADR / RID, IMDG, IATA: | 1263 |
|------------------------|------|

**14.2. UN proper shipping name**

|            |                         |
|------------|-------------------------|
| ADR / RID: | PAINTE RELATED MATERIAL |
| IMDG:      | PAINTE RELATED MATERIAL |
| IATA:      | PAINTE RELATED MATERIAL |

**14.3. Transport hazard class(es)**

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



**14.4. Packing group**

ADR / RID, IMDG, IATA: III

**14.5. Environmental hazards**

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

**14.6. Special precautions for user**

|            |  |  |  |
|------------|--|--|--|
| ADR / RID: | HIN - Kemler: 30<br>Special provision: 163, 367, 650 | Limited Quantities: 5 L  | Tunnel restriction code: (D/E)                             |
| IMDG:      | EMS: F-E, <u>S-E</u>                                 | Limited Quantities: 5 L  |  |
| IATA:      | Cargo:<br>Passengers:<br>Special provision:          | Maximum quantity: 220 L<br>Maximum quantity: 60 L<br>A3, A72, A192 | Packaging instructions: 366<br>Packaging instructions: 355 |

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: P5c-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 3 - 40

## SurfaDur P Pool, Part B

Contained substance

|       |    |               |
|-------|----|---------------|
| Point | 75 |               |
| Point | 74 | DIISOCYANATES |

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

|                     |  |
|---------------------|--|
| <b>Flam. Liq. 3</b> | Flammable liquid, category 3                                   |
| <b>Acute Tox. 4</b> | Acute toxicity, category 4                                     |
| <b>Asp. Tox. 1</b>  | Aspiration hazard, category 1                                  |
| <b>STOT RE 2</b>    | Specific target organ toxicity - repeated exposure, category 2 |

|                          |  |
|--------------------------|--|
| <b>Eye Irrit. 2</b>      | Eye irritation, category 2   |
| <b>Skin Irrit. 2</b>     | Skin irritation, category 2  |
| <b>STOT SE 3</b>         | Specific target organ toxicity - single exposure, category 3               |
| <b>Resp. Sens. 1</b>     | Respiratory sensitization, category 1                                      |
| <b>Skin Sens. 1</b>      | Skin sensitization, category 1   |
| <b>Skin Sens. 1B</b>     | Skin sensitization, category 1B  |
| <b>Aquatic Chronic 2</b> | Hazardous to the aquatic environment, chronic toxicity, category 2         |
| <b>H226</b>              | Flammable liquid and vapour.   |
| <b>H302</b>              | Harmful if swallowed.  |
| <b>H312</b>              | Harmful in contact with skin.  |
| <b>H332</b>              | Harmful if inhaled.  |
| <b>H304</b>              | May be fatal if swallowed and enters airways.                              |
| <b>H373</b>              | May cause damage to organs through prolonged or repeated exposure.         |
| <b>H319</b>              | Causes serious eye irritation.   |
| <b>H315</b>              | Causes skin irritation.  |
| <b>H335</b>              | May cause respiratory irritation.  |
| <b>H334</b>              | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| <b>H317</b>              | May cause an allergic skin reaction.                                       |
| <b>H336</b>              | May cause drowsiness or dizziness.   |
| <b>H411</b>              | Toxic to aquatic life with long lasting effects.                           |
| <b>EUH066</b>            | Repeated exposure may cause skin dryness or cracking.                      |
| <b>EUH204</b>            | Contains isocyanates. May produce an allergic reaction.                    |

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).



**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
  22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.